











GENERAL

DESIGN Robert Allan Ltd. TRAktor 2600-Z
BASIC FUNCTIONS Towing, pushing, mooring, fire-fighting
CLASSIFICATION RINA

C 掛HULL, 掛MACH, 承 AUT-UMS, TUG FIREFIGHTING SHIP1 WITH WATER SPRAY UNRESTRICTED NAVIGATION, MLC DESIGN INWATERSURVEY

DIMENSIONS

 LENGTH 0.A.
 26,00 m

 BEAM
 12.20 m

 DEPTH
 4,55 m

 DRAFT BASELINE
 6,15 m

 DRAFT EXTREME
 6,35 m

 GROSS TONNAGE
 < 400</td>

TANK CAPACITIES

FUEL 0IL $100,0~0~m^3$ FRESH WATER $12,00~m^3$

PERFORMANCES

BOLLARD PULL 75 tons
SPEED 12,5 knots (approx.)

PROPULSION SYSTEM

MAIN ENGINES

CATERPILLAR 3516C

TOTAL POWER

EMISSION STANDARD

AZIMUTHING STERN DRIVE

CONGSBERG US255 FP

PROPELLERS

CATERPILLAR 3516C

2 x 2240 kW @ 1600 rpm

IMO Tier II

SCHOTTEL SRP 460 FP /

KONGSBERG US255 FP

2600 mm diameters

Built-in, Hydraulically Operated ON/OFF Clutch

(Optional HD Slipping Clutch - for Fi-Fi 1)

SHAFTING Carbon Fiber Shaft

ACCOMMODATION

Accommodation for 6 people MLC-compliant high-quality and great comfort accommodation is climate-controlled and includes a captain's cabin, an officer cabin, and two double crew cabins.

DECK EQUIPMENT

AFT TOWING WINCH Two (2) THR MARINE single drum, electrical driven

winches with hydraulic operated band brake and

hydraulic operated friction clutch.

Force and speed ranges: 250 kN at 9 m/min

80 kN at 28 m/min

Brake holding force in 1st layer: 1750 kN

ANCHORS & CHAIN Class Requirements

FENDERS Rubber, Cylinder, W and D type fendering

AUXILIARY EQUIPMENT

GENERATOR SET 2 x C4.4 86 ekW 1500 rpm 50hz

FRESH WATER SYSTEM Hydrophore and UV filter combined heater

MACHINERY COOLING SYSTEM Box cooler type
AIR-CONDITIONING HEINEN HOPMAN:

Secondary AC unit in wheelhouse

Cold climate package

Hot climate package

2x M/E driven Fi-Fi pump

FIFI 1 SYSTEM 2x M/E driven Fi-Fi pump

Capacity (each); 1350 m³/hr.

2x Monitor: Foam/water monitor with remote

operated, electric controls

NAUTICAL AND COMMUNICATION EQUIPMENT

GMDSS A3 AREA

SEARCHLIGHT 2 x 230 V, 2000 W **RADAR** FURUNO FAR-1518-BB FURUNO GP-170 **GPS NAVIGATOR** FURUNO FA-170 AIS CLAS A SATELLITE COMPASS FURUNO SC-70 MAGNETIC COMPASS REFLECTA A/3 NAVTEX FURUNO NX-700B **EPIRB** JOTRON TRON 60S SART JOTRON TRON SART 20 **AUTOPILOT RAYTHEON ANSCHUTZ NP 60**

BNWAS FURUNO BR-500
INTERCOM PHONTECH CIS-3100
VHF JOTRON TRON TR30
INMARSAT-C FELCOM-19/SSAS
ANOMOMETER AIRMAR 220WX
SPEED LOG FURUNO DS-80
ECHO SOUNDER FURUNO: FE-800

OPTIONAL EQUIPMENT

DECK CRANE PALFINGER PK18500(M)B SWL 1t@10m

RESCUE BOAT CRANE PALFINGER SCH 12-3.5 R SWL 12t@3.5m

RESCUE BOAT RIBO DSB 5.1 SR/SOLAS
CAPSTAN DATA HIDROLIK SWL:5t
TOWING HOOK One (1) or Two (2) on aft deck

DATA HIDROLIK quick release disc type

Type DTH 90-135 P





www.medmarine.com.tr



www.ereglishipyard.com

